






**GEAR TRANSMISSION UNIT WITH PLANET CARRIER****Patent number:** WO2004013516**Publication date:** 2004-02-12**Inventor:** FLAMANG PETER (BE)**Applicant:** HANSEN TRANSMISSIONS INT (BE);; FLAMANG PETER (BE)**Classification:****- international:** F16H1/28; F03D11/02**- european:** F03D11/02; F16H57/08B**Application number:** WO2003IB03754 20030731**Priority number(s):** GB20020018557 20020812; WO2002IB03596 20020801**Also published as:** AU2003259411 (A1)**Cited documents:** WO0214690 WO9611338 DE2235448 WO02079644**Report a data error here****Abstract of WO2004013516**

A planetary type gear transmission unit suitable for a wind turbine comprises sun (27), planet (25) and ring (24) gears and a planet carrier (41), the planet carrier comprising a planet bogie plate (43) which supports and locates circumferentially spaced planet gear bearings (45, 46) on which the planet gears are mounted, and at least some of said bearings (45, 46) being cylindrical roller bearings.

Data supplied from the **esp@cenet** database - Worldwide

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)


PCT

(10) International Publication Number  
**WO 2004/013516 A1**

- (51) International Patent Classification<sup>7</sup>: **F16H 1/28**, (74) Agent: **BADGER, John, Raymond**; Invensys Intellectual Property, P.O. Box 8433, Redditch B98 0DW (GB).  
F03D 11/02
- (21) International Application Number: **PCT/IB2003/003754**
- (22) International Filing Date: **31 July 2003 (31.07.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
PCT/IB02/03596 1 August 2002 (01.08.2002) IB  
0218557.7 12 August 2002 (12.08.2002) GB
- (71) Applicant (for all designated States except US): **HANSEN TRANSMISSIONS INTERNATIONAL NV [BE/BE]**; Leonardo Da Vincilaan 1, B-2650 Edegem, Antwerp (BE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **FLAMANG, Peter [BE/BE]**; Hansen Transmissions International NV, Leonardo Da Vincilaan 1, B-2650 Edegem, Antwerp (BE).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published:  
— with international search report

[Continued on next page]

(54) Title: **GEAR TRANSMISSION UNIT WITH PLANET CARRIER**



(57) Abstract: A planetary type gear transmission unit suitable for a wind turbine comprises sun (27), planet (25) and ring (24) gears and a planet carrier (41), the planet carrier comprising a planet bogie plate (43) which supports and locates circumferentially spaced planet gear bearings (45, 46) on which the planet gears are mounted, and at least some of said bearings (45, 46) being cylindrical roller bearings.

WO 2004/013516 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## GEAR TRANSMISSION UNIT WITH PLANET CARRIER

This invention relates to a planet carrier for a gear transmission unit and in particular, though not exclusively, to a planetary type gear transmission unit. It may be applied to a gear transmission unit for a wind turbine.

There is a continuing demand for larger wind turbines especially for offshore sites due to scarcity of suitable sites and cost of civil works. At the same time the requirements for reduction of size and weight of the machines and their components become more and more important. Typically a wind turbine rotor drives the low speed shaft of a gear transmission unit, which transforms torque and speed of the rotor to the required torque and speed of an electrical generator.

Integration of the components in a wind turbine is a way to reduce the weight and to make the drive assembly more compact, but it is important that the design and execution of the drive assembly avoids mutual interference of the external and internal loads on the different components. It is also important that the construction of an integrated drive assembly allows effective lubrication to be achieved economically and reliably.

The present invention is directed particularly but not exclusively to the problem of providing an accurate and long life support for planet gears in a manner which is economical and which may be utilized on a wind turbine assembly.

In accordance with one aspect of the present invention a planetary type gear transmission unit comprises sun, planet and ring gears and a planet carrier, said planet carrier comprising a planet bogie plate which supports and locates circumferentially spaced planet gear bearings on which planet gears are mounted, and at least some of said bearings being cylindrical roller type bearings.

The gear unit may comprise planet gears which are arranged in axially aligned pairs.

The bearings may support respective pairs of aligned planet gears, typically the two gears of each pair being positioned at opposite sides of the plate.

The bearing(s) for each circumferentially spaced planet gear position may be supported on a shaft which in use is able to self adjust in said angular position relative to the bogie plate.

As considered in an axial direction parallel with the axis of rotation of the planet carrier, a main bearing for rotatably supporting a ring gear relative to a planet carrier lies at a position substantially aligned axially with the axial position of at least the ring gear of the gear transmission unit.

Preferably the sun, planet and ring gears lie in a transverse plane (perpendicular to the rotation axis of said rotational forces) which also contains said main bearing.

The ring gear may provide axial and radial locations for the main bearing. The ring gear may have a radially outer surface of a stepped profile to define a shoulder for axial location of an inner bearing ring of the main bearing. The inner bearing ring may be secured axially and non-rotatably between said shoulder and a supporting structure.

The ring gear may be provided with a reinforcing ring, and said reinforcing ring may extend axially and or radially beyond the toothed surface of the ring gear. Said reinforcing ring may provide an axial location of the main bearing.

The main bearing may comprise a double taper bearing, and said double taper bearing may comprise a single outer bearing ring. The double taper bearing may comprise rollers arranged in an O configuration in which the rollers of one series increase in diameter in a direction away from the rollers of the other series of the pair.

In a yet further of its aspects the present invention provides a wind turbine comprising rotors, a generator and a drive assembly comprising a gear transmission unit of a type in accordance with the present invention. In said drive assembly the ring gear typically may be supported non-rotatably relative to supporting structure.

A part of the gear transmission unit, e.g. a housing thereof, may be arranged to support an electrical generator.

The invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which: -

Figure 1 is an elevation view of a wind turbine having a gear transmission unit of the present invention;

Figure 2 is a sectional view of part of a gear transmission unit;

Figure 3 shows part of Figure 2 in more detail, and

Figure 4 shows a particular feature of the present invention.

A wind turbine 10 (see Figure 1) comprises a gear transmission unit 11 which acts to transmit torque from rotor blades 12 and a rotor hub 14 to an electrical generator 13, the gear transmission unit comprising an epicyclic gear unit. The gear transmission unit and generator are housed in and supported by a nacelle 15.

The gear transmission unit 11 is now described in more detail with reference to Figures 2 and 3. The gear transmission unit 11 comprises an epicyclic gear unit having four circumferentially spaced planet gears 25, a sun gear 27 a planet carrier 28, and a ring gear 24 which is non-rotatably mounted relative to the nacelle structure 15.

The sun gear is connected to an output shaft (not shown) which connects either to a further gear unit or direct to the rotor of the generator 13.

The radially outer surface 29 of the ring gear 24 provides location and support for the inner ring 30 of a main bearing 23.

The outer ring 31 of the main bearing has secured thereto the rotor hub 14 and, interposed between the rotor hub and ring 31, the outer region 22 of the planet carrier 28.

In a prior proposed construction the planet carrier 28 of Figure 3 comprises four bearing support studs 26 uniformly circumferentially spaced to locate bearings 32 which rotatably support the four planet gears 25. The planet carrier 28 has an annular region 33 which extends radially between the radial position of the bearing studs 26 and the outer region 22 and is designed to be relatively stiff, in a circumferential direction about the Y axis, for transmission of torque between the region 22 and the bearing studs 26, but to be relatively flexible about the X and Z axis.

In accordance with the present invention the planet carrier 28 is replaced by a planet carrier 41 (see Figure 4) provided, in this embodiment, with three integral and uniformly circumferentially spaced studs 42 which support a planet bogie plate 43. The planet bogie plate 43 provides support for three circumferentially uniformly spaced shafts 44 arranged each (as viewed in the plane of Figure 4) to self adjust in angular position on the plate 43. Each shaft 44 provides support, at opposite sides of the plate 43, for a pair of cylindrical roller bearings 45, 46 about which each of a pair of planet gears 47, 48 are rotatably mounted for engagement with the ring gear 49.

In the aforescribed construction the torque acting on the rotor hub 14 under action of the rotor blades 12 is transmitted to the planet gears 47, 48 via the planet carrier 41 rotatably mounted at its outer region to the outer ring 31 of bearing 23. Bending moments and axial forces in the Y direction exerted by the rotor hub in this construction are transmitted direct to the bearing 23. The flexibility of the annular portion 33 of the planet carrier 28 assists to substantially isolate those forces from the planet gears.

The present invention thus teaches, in its broadest aspect, that a bogie of a planet carrier is provided with roller bearings which are of the cylindrical type for the support of planet gears.



**CLAIMS**

1. A planetary type gear transmission unit comprises sun, planet and ring gears and a planet carrier, said planet carrier comprising a planet bogie plate which supports and locates circumferentially spaced planet gear bearings on which planet gears are mounted, and at least some of said bearings being cylindrical roller bearings.
2. A gear transmission unit according to claim 1, wherein it comprises planet gears arranged in axially aligned pairs.
3. A gear transmission unit according to claim 2, wherein the bearings support respective pairs of aligned planet gears.
4. A gear transmission unit according to claim 3, wherein two gears of each pair are positioned at opposite sides of the plate.
5. A gear transmission unit according to any one of the preceding claims, wherein the bearings for each circumferentially spaced planet gear position are supported on a shaft which, in use, self adjusts in said angular position relative to the bogie plate.
6. A gear transmission unit according to any one of the preceding claims, wherein, as considered in an axial direction parallel with the axis of rotation of the planet carrier, the ring gear is substantially aligned axially with a main bearing which supports the ring gear relative to the planet carrier.
7. A gear transmission unit according to claim 6, wherein the main bearing comprises an inner ring bearing surface of a diameter greater than that of the toothed surface of the ring gear.
8. A gear transmission unit according to claim 6 or claim 7, wherein the sun, planet and ring gears lie in a transverse plane which contains said main bearing.
9. A gear transmission unit according to any one of the preceding claims wherein the planet carrier provides a radially extending torque transmissions path

which is torsionally stiff but relatively compliant in an axial direction parallel with the axis about which the rotational forces act.

10. A gear transmission unit according to claim 1, and substantially as hereinbefore described.







FIG. 1

**FIG. 2**

**FIG. 3**



**FIG. 4**

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IB 03/03754

**A. CLASSIFICATION OF SUBJECT MATTER**  
 IPC 7 F16H1/28 F03D11/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
 IPC 7 F16H F03D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 02 14690 A (HANSEN TRANSMISSIONS INTERNAT ; BOGAERT ROGER (BE); FLAMANG PETER ( ) 21 February 2002 (2002-02-21) page 5, paragraph 1 - page 6, paragraph 2 figures 1-4	1-10
X	WO 96 11338 A (HEHENBERGER GERALD) 18 April 1996 (1996-04-18) figures 3-7	1-6, 9, 10
A		7, 8
X	DE 22 35 448 A (FLENDER A F & CO) 7 February 1974 (1974-02-07) page 4 figures 1, 2	1-6, 9, 10
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

**\* Special categories of cited documents :**

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

10 November 2003

Date of mailing of the international search report

02/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentplan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Hassiotis, V

## INTERNATIONAL SEARCH REPORT

Internatio      pplication No

PCT/IB 03/03754

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 02 079644 A (CHRISTENSEN MOGENS ; VESTAS WIND SYSTEMS AS (DK)) 10 October 2002 (2002-10-10) the whole document -----	1-10



Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 0214690	A	21-02-2002	AU	7659301 A		25-02-2002
			CN	1447880 T		08-10-2003
			EP	1311759 A1		21-05-2003
			WO	0214690 A1		21-02-2002
WO 9611338	A	18-04-1996	AT	403310 B		26-01-1998
			WO	9611338 A1		18-04-1996
			AT	209753 T		15-12-2001
			AU	3597095 A		02-05-1996
			DE	59509888 D1		10-01-2002
			EP	0792415 A1		03-09-1997
			ES	2166832 T3		01-05-2002
			AT	216694 A		15-05-1997
DE 2235448	A	07-02-1974	DE	2235448 A1		07-02-1974
WO 02079644	A	10-10-2002	DK	200100545 A		03-06-2002
			WO	02079644 A1		10-10-2002

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**